



**Roue** : polyuréthane Shore 85 A  
**Jante** : polyamide  
**Moyeu** : lisse ( L ) à rouleaux ( R ) ou roulements à billes ( B ) + PARE FILS  
 Existent à moyeux à rouleaux et roulements INOX

									REFERENCE 	REFERENCE 	REFERENCE 	CODE
80	30	39	12	39	12	40	8	75	NP080S85L	NP080S85R	NP080S85B	9
80	30	---	---	39	12	40	8	75	---	NPX080S85R	NPX080S85B	9
100	30	44	12	44	12	45	8	120	NP100S85L	NP100S85R	NP100S85B	9
100	30	---	---	44	12	45	8	120	---	NPX100S85R	NPX100S85B	9
125	35	44	15	44	15	45	8	180	NP125S85L	NP125S85R	NP125S85B	9
125	35	---	---	44	15	45	8	180	---	NPX125S85R	NPX125S85B	9
150	35	44	15	44	15	---	---	220	NP150S85L	NP150S85R	---	9
150	45	59	20	59	20	---	---	240	NP151S85L	NP151S85R	---	9
200	50	59	20	59	20	---	---	300	NP200S85L	NP200S85R	---	9



**Roue** : polyuréthane Shore 95  
**Jante** : polyamide  
**Moyeu** : roulements à billes + PARE FILS Existent à moyeux à rouleaux et roulements INOX  
**Temp.d'utilisation** : -25°C + 60°C

					REFERENCE 	REFERENCE 	CODE
80	30	40	8	100	080NPB	080NPBX	F
100	30	40	8	150	100NPB	100NPBX	F
125	30	50	10	200	125NPB	125NPBX	F
160	40	60	12	250	160NPB	160NPBX	F
200	50	60	12	300	200NPB	200NPBX	F



**Roue** : polyuréthane Shore 95 profil bombé  
**Jante** : polyamide  
**Moyeu** : lisse ( L ) ou à rouleaux ( R )  
**Temp.d'utilisation** : -25°C + 60°C

					REFERENCE 	REFERENCE 	CODE
80	28	40	12	100	080NPBL	080NPBR	8
100	30	40	12	150	100NPBL	100NPBR	8
125	32	44	15	200	125NPBL	125NPBR	8
160	38	58	20	320	160NPBL	160NPBR	8
200	45	58	20	380	200NPBL	200NPBR	8










**Roue :** polyuréthane Shore 95

**Jante :** polyamide

**Moyeu :** lisse ( L ) et à rouleaux ( R )

**Temp.d'utilisation :** -25°C + 60°C



					REFERENCE 	REFERENCE 	CODE
60	24	29	8	60	NP060L8	---	F
80	30	40	12	120	NP080L12	NP080R12	8
80	30	40	12	150	NP081L12	NP081R12	F
80	32	44	12	150	NP082L12	NP082R12	8
100	30	40	12	170	NP100L12	NP100R12	8
100	30	40	12	180	NP101L12	NP101R12	F
100	30	45	12	170	NP102L12	NP102R12	8
100	40	49	15	350	NP103L15	NP103R15	F
125	32	45	12	225	NP125L12	NP125R12	8
125	35	49	15	250	NP126L15	NP126R15	F
125	45	49	20	400	NP127L20	NP127R20	F
125	45	58	20	500	NP128L20	NP128R20	8
150	40	44	15	280	NP150L15	NP150R15	8
150	40	49	20	350	NP151L20	NP151R20	F
150	45	58	20	600	NP152L20	NP152R20	8
150	50	59	20	600	NP153L20	NP153R20	F
160	40	58	20	480	NP160L20	NP160R20	F
160	45	60	20	300	NP161L20	NP161R20	8
160	50	59	20	700	NP162L20	NP162R20	F
175	45	59	20	550	NP175L20	NP175R20	F
200	50	58	20	450	NP200L20	NP200R20	8
200	50	59	20	550	NP201L20	NP201R20	F
200	50	58	20	750	NP202L20	NP202R20	8
200	55	60	25	1000	NP203L25	NP203R25	F
250	60	75	25	800	NP250L25	NP250R25	F







**Roue :** polyuréthane Shore 95

**Jante :** polyamide

**Moyeu :** roulements à billes

**Temp.d'utilisation :** -25°C + 60°C



					REFERENCE 		CODE
100	40	40	15	350	NP100B15		F
125	45	49	20	400	NP125B20		F
150	50	55	20	600	NP150B20		F
160	50	55	20	700	NP160B20		F
200	55	60	25	1000	NP200B25		F