









Roue : polyuréthane Shore 95

Jante : polyamide

Moyeu : roulements à billes

Temp.d'utilisation : -25°C + 60°C

					REFERENCE 		CODE
60	24	17	15	60	NP060B15		F
80	30	30	12	150	NP081B12		F
100	35	44	8	180	NP100B08		8
100	30	35	15	180	NP101B15		F
125	35	45	8	225	NP125B080		8
125	35	35	15	250	NP126B15		F
125	45	58	20	500	NP127B20		8
150	40	47	20	350	NP151B20		F
160	40	55	20	480	NP161B20		F
160	45	60	20	400	NP162B20		8
175	45	55	20	550	NP175B20		F
200	50	55	20	550	NP201B20		F
200	50	58	20	750	NP202B20		8
250	60	62	25	800	NP250B25		F









Roue : polyuréthane Shore 95 POUR FORTES CHARGES polyuréthane coulé.

Jante : polyamide

Moyeu : roulements à billes

Temp.d'utilisation : -25°C + 60°C

					REFERENCE 		CODE
80	30	36	15	230	NPP080		F
100	30	36	15	250	NPP100		F
125	40	47	15	400	NPP125		F
150	40	47	20	500	NPP150		F
150	40	47	25	500	NPP151		F
200	50	52	20	850	NPP200		F
200	5	52	25	850	NPP201		F