













Roue : polyuréthane Shore 75
Jante : aluminium
Moyeu : roulements à billes
Temp.d'utilisation : -25°C + 70°C

					REFERENCE =		CODE
100	40	40	15	300	ALPU100B15S75		9059
125	40	40	20	350	ALPU125B20S75		9059
125	40	50	20	350	ALPU126B20S75		9059
160	50	58	20	550	ALPU160B20S75		9059
160	50	58	25	550	ALPU160B25S75		9059
180	50	60	20	600	ALPU180B20S75		9059
200	50	60	20	700	ALPU200B20S75		9059
200	50	60	25	700	ALPU200B25S75		9059
250	50	55	20	700	ALPU250B20S75		9059








Roue : polyuréthane Shore 83 +-3
Jante : aluminium
Moyeu : roulements à billes
Temp.d'utilisation : -25°C + 70°C

					REFERENCE =		CODE
125	50	60	20	400	ALP125B20S83		8
160	50	60	20	550	ALP160B20S83		8
200	50	60	20	700	ALP200B20S83		8
250	50	60	25	800	ALP250B25S83		8



Roue : polyuréthane Shore 83 +-3 profil bombé
Jante : aluminium
Moyeu : à billes
Temp.d'utilisation : -25°C + 70°C

					REFERENCE =		CODE
80	40	45	15	180	ALP080B15S83		8
100	40	45	15	200	ALP100B15S83		8
100	50	60	20	350	ALP101B20S83		8
125	40	45	15	300	ALP125B15S83		8
125	50	60	20	400	ALP126B20S83		8
160	50	60	20	550	ALP160B20S83		8
200	50	60	20	700	ALP200B20S83		8
200	50	60	25	700	ALP201B25S83		8