








Roue : polyuréthane SHORE 93

Jante : fonte

Moyeu : roulements à billes

Temp.d'utilisation : -25°C + 70°C

					REFERENCE		CODE
50	15	15	15	100	FPU050B15		F
50	18	18	15	100	FPU051B15		F
63	25	30	8	115	FPU063B08		8
75	25	40	10	160	FPU075B10		8
80	20	20	12	150	FPU080B12		F
80	20	25	15	200	FPU081B15		F
80	25	25	15	200	FPU082B15		F
80	30	40	15	220	FPU083B15		F
80	36	36	15	250	FPU084B15		F
100	25	35	15	200	FPU100B15		F
100	29	40	12	230	FPU101B12		8
100	30	30	15	250	FPU102B15		F
100	30	36	15	250	FPU103B15		F
100	38	45	20	300	FPU104B20		8
100	38	45	25	300	FPU105B25		8
100	40	40	15	350	FPU106B15		F
100	40	40	20	350	FPU107B20		F
100	40	45	15	350	FPU108B15		F
100	40	45	20	350	FPU109B20		F
100	50	60	20	500	FPU100B20		F
125	28	47	15	300	FPU125B15		F
125	30	30	15	300	FPU126B15		F
125	32	45	12	280	FPU127B12		8
125	35	47	15	330	FPU128B15		F
125	38	45	20	400	FPU129B20		8
125	38	60	20	400	FPU0125B20		8
125	38	60	25	400	FPU0126B25		8
125	40	40	15	360	FPU0127B15		F
125	40	47	15	360	FPU0128B15		F
125	40	60	17	400	FPU0129B17		F
125	40	60	20	400	FPU0125B20		F
125	50	60	20	500	FPU126B20		8-F
125	60	60	20	700	FPU127B20		F
125	60	60	25	700	FPU128B25		F
150	30	47	20	400	FPU150B20		F
150	30	47	25	400	FPU150B25		F
150	38	60	20	600	FPU151B20		8
150	38	60	25	600	FPU151B25		8









Roue : polyuréthane SHORE 93

Jante : fonte

Moyeu : roulements à billes

Temp.d'utilisation : -25°C + 70°C

					REFERENCE 		CODE
150	38	60	30	600	FPU150B30		8
150	40	47	20	500	FPU152B20		F
150	40	47	25	500	FPU152B25		F
150	40	40	20	500	FPU150B20M40		F
150	40	40	25	500	FPU150B25M40		F
150	40	60	20	500	FPU150B20M60		F
150	40	60	25	500	FPU150B25M60		F
150	50	60	20	700	FPU153B20		8-F
150	50	60	25	700	FPU153B25		8-F
150	50	50	20	700	FPU154B20		F
150	50	60	25	700	FPU154B25		F
150	57	60	20	800	FPU155B20		8
150	57	60	25	800	FPU155B25		8
150	57	60	30	800	FPU155B30		8
150	60	60	20	930	FPU156B20		F
150	60	60	25	930	FPU156B25		F
150	60	65	20	930	FPU156B20M65		F
150	60	65	25	930	FPU156B25M65		F
150	80	90	25	1000	FPU157B25		8
150	80	90	30	1000	FPU157B30		8
160	40	60	20	700	FPU160B20		F
160	40	60	25	700	FPU160B25		F
160	50	60	20	750	FPU161B20		8
160	50	60	25	750	FPU161B25		8
160	50	60	20	800	FPU162B20		F
160	50	60	25	800	FPU162B25		F
160	75	90	25	1000	FPU163B25		8
160	75	90	30	1000	FPU163B30		8
160	75	90	35	1000	FPU163B35		8
175	32	52	20	650	FPU175B20		F
175	32	52	25	650	FPU175B25		F
175	40	52	20	720	FPU176B20		F
175	40	52	25	720	FPU176B25		F
175	40	40	20	700	FPU175B20M40		F
175	40	40	25	700	FPU175B25M40		F
175	60	60	20	960	FPU177B20		F
175	60	60	25	960	FPU177B25		F
180	50	60	20	900	FPU180B20		F









Roue : polyuréthane SHORE 93

Jante : fonte

Moyeu : roulements à billes

Temp.d'utilisation : -25°C + 70°C

					REFERENCE 		CODE
180	50	60	25	900	FPU180B25		F
200	40	52	20	750	FPU200B20		F
200	40	52	25	750	FPU200B25		F
200	40	45	20	750	FPU200B20M45		F
200	40	45	25	750	FPU200B25M45		F
200	44	60	20	900	FPU201B20		8
200	44	60	25	900	FPU201B25		8
200	50	50	20	830	FPU200B20M50		F
200	50	50	25	830	FPU200B25M50		F
200	50	52	20	1000	FPU200B20M52		F
200	50	52	25	1000	FPU200B25M52		F
200	50	60	20	1000	FPU200B20M60		8-F
200	50	60	25	1000	FPU200B25M60		8-F
200	57	60	20	1100	FPU201B20		8
200	57	60	25	1100	FPU201B25		8
200	57	60	30	1100	FPU201B30		8
200	60	60	20	1200	FPU202B20M60		F
200	60	60	25	1200	FPU202B25M60		F
200	60	65	20	1200	FPU202B20M65		F
200	60	65	25	1200	FPU202B25M65		F
200	75	90	25	1400	FPU203B25		8
200	75	90	30	1400	FPU203B30		8
200	75	90	35	1400	FPU203B35		8
200	80	80	30	1500	FPU204B30		F
200	80	80	35	1500	FPU204B35		F
200	100	100	30	1950	FPU205B30		F
200	100	100	35	1950	FPU205B35		F
225	50	50	20	1000	FPU225B20		F
225	50	50	25	1000	FPU225B25		F
250	44	60	25	1100	FPU250B25		8
250	44	60	30	1100	FPU250B30		8
250	44	60	35	1100	FPU250B35		8
250	50	60	20	1200	FPU251B20		8-F
250	50	60	25	1200	FPU251B25		8-F
250	57	60	25	1400	FPU252B25		8
250	57	60	30	1400	FPU252B30		8
250	57	60	35	1400	FPU252B35		8
250	60	60	20	1500	FPU253B20		F
250	60	60	25	1500	FPU253B25		F









Roue : polyuréthane SHORE 93

Jante : fonte







Moyeu : roulements à billes

Temp.d'utilisation : -25°C + 70°C

					REFERENCE 		CODE
250	60	65	20	1500	FPU250B20M65		F
250	60	65	25	1500	FPU250B25M65		F
250	75	90	25	1800	FPU254B25		8
250	75	90	30	1800	FPU254B30		8
250	75	90	35	1800	FPU254B35		8
250	80	80	30	1800	FPU255B30		F
250	80	80	35	1800	FPU255B35		F
250	100	100	30	2200	FPU256B30		F
250	100	100	35	2200	FPU256B35		F
250	100	120	30	2200	FPU257B30		8
250	100	120	35	2200	FPU257B35		8
300	44	60	25	1150	FPU300B25		8
300	44	60	30	1150	FPU300B30		8
300	44	60	35	1150	FPU300B35		8
300	50	60	25	1300	FPU301B25		8
300	50	60	30	1300	FPU301B30		8
300	50	60	35	1300	FPU301B35		8
300	57	60	25	1500	FPU302B25		8
300	57	60	30	1500	FPU302B30		8
300	57	60	35	1500	FPU302B35		8
300	70	70	30	2100	FPU303B30		F
300	70	70	35	2100	FPU303B35		F
300	75	90	25	2000	FPU304B25		8
300	75	90	30	2000	FPU304B30		8
300	75	90	35	2000	FPU304B35		8
300	75	90	40	2000	FPU304B40		8
300	75	90	50	2000	FPU304B50		8
300	80	80	30	2200	FPU305B30		F
300	80	80	35	2200	FPU305B35		F
300	100	120	35	2500	FPU306B35		8
300	100	120	40	2500	FPU306B40		8
300	100	120	50	2500	FPU306B50		8
300	100	100	40	3000	FPU307B40		F
350	100	100	40	3500	FPU350B40		F
350	100	100	50	3500	FPU350B50		F
400	80	100	40	3300	FPU400B40		F
400	80	100	50	3300	FPU400B50		F
400	100	120	40	3100	FPU401B40		8
400	100	120	50	3100	FPU401B50		8



**Roue :** polyuréthane SHORE 93  
**Jante :** fonte ou acier \* ( APU )  
**Moyeu :** à billes  
**Temp.d'utilisation :** -25°C + 70°C







					REFERENCE 		CODE
400	100	120	55	3100	FPU401B55		8
400	100	100	40	3800	FPU402B40		F
400	100	100	50	3800	FPU402B50		F
400	125	125	40	4500	FPU403B40		F
400	125	125	50	4500	FPU403B50		F
400	125	125	50	5000	FPU404B50		8
400	125	125	55	5000	FPU404B55		8
400	125	125	60	5000	FPU404B60		8
500	100	100	50	4500	FPU500B50		F
500	100	100	55	4500	FPU500B55		F
500	120	120	40	4500	APU501B40*		9172
500	120	120	50	4500	APU501B50*		9172
500	150	150	60	6000	APU502B60*		9172
500	200	200	60	6500	APU503B60*		9172

**TOUTE AUTRE DIMENSION SUR DEMANDE**

**TOUTES NOS ROUES FONTE OU ACIER PEUVENT ETRE REVETUES DE VULKOLLAN®**



**Roue :** polyuréthane SHORE 93 ANTISTATIQUE  
**Jante :** fonte  
**Moyeu :** roulements à billes  
**Temp.d'utilisation :** -25°C + 70°C

					REFERENCE 		CODE
80	36	36	15	220	FPU080B15AS		F
100	30	36	15	220	FPU100B15AS		F
125	35	47	15	290	FPU125B15AS		F
150	40	47	20	440	FPU150B20AS		F
160	40	60	20	610	FPU160B20AS		F
175	40	52	20	630	FPU175B20AS		F
200	50	52	25	880	FPU200B20AS		F





