













Roue : FONTE
 Moyeu : LISSE
 Temp.d'utilisation : -40°C +500°C
 Série ajourée

ROUES FONTE

					REFERENCE		CODE
80	30	39	15	150	FO080ML15		F
100	30	39	15	200	FO100ML15		F
125	35	49	15	240	FO125ML15		F
150	40	49	20	300	FO150ML20		F
175	50	58	20	430	FO175ML20		F
200	50	58	20	480	FO200ML20		F








Roue : FONTE
 Moyeu : LISSE
 Temp.d'utilisation : -40°C +500°C

					REFERENCE		CODE
63	25	30	10	130	FO063ML10		8
75	25	30	10	140	FO075ML10		8
75	34	45	12	200	FO075ML12		8
85	30	36	15	270	FO085ML15		F
85	30	36	20	270	FO085ML20		F
100	38	45	12	250	8FO100ML12		8
100	35	45	20	400	8FO100ML20		8
100	35	45	25	400	8FO100ML25		8
105	35	47	15	450	FO105ML105		F
105	35	45	20	450	F0105ML20		F
125	35	45	20	500	8FO125ML20		8
125	40	60	20	600	8FO126ML20		8
130	40	47	20	700	FO130ML20		F
130	40	47	25	700	FO130ML25		F
150	40	52	20	900	FO150ML20		F
150	40	52	25	900	FO150ML25		F
150	45	60	20	1000	8FO151ML20		8
150	40	60	25	700	8FO152ML20		8
150	40	60	30	700	8FO153ML30		8
160	40	60	25	800	8FO160ML25		8
160	40	60	30	800	8FO160ML30		8
175	50	52	20	1200	FO175ML20		F
175	50	52	25	1200	FO175ML25		F
200	45	60	25	1000	8FO200ML25		8



Roue : FONTE






Moyeu : roulements à billes

					REFERENCE		CODE
80	40	45	15	350	FO080B15		F
80	40	47	15	350	FO081B15		F
80	40	40	15	350	FO082B15		F
85	25	36	15	250	FO085B15		F
85	30	36	15	270	FO086B15		F
100	35	45	20	400	FO100B20		8
100	35	45	25	400	FO100B25		8
100	50	60	20	450	FO101B20		8
105	28	45	15	400	FO105B15		F
105	35	47	15	450	FO106B15		F
105	40	47	15	500	FO107B15		F
105	50	60	20	600	FO105B20		F
125	35	45	20	500	FO125B20		8
125	40	60	20	600	FO126B20		8
125	40	60	25	600	FO126B25		8
130	30	47	20	600	FO130B20		F
130	30	47	25	600	FO130B25		F
130	40	47	20	700	FO131B20		F
130	40	47	25	700	FO131B25		F
130	50	50	20	1000	FO132B20		F
130	50	50	25	1000	FO132B25		F
130	60	65	20	1200	FO133B20		F
130	60	65	25	1200	FO133B25		F
150	32	52	20	800	FO150B20		F
150	32	52	25	800	FO150B25		F
150	40	52	20	900	FO151B20		F
150	40	52	25	900	FO151B25		F
150	40	60	20	700	FO152B20		8
150	40	60	25	700	FO152B25		8
150	40	60	30	700	FO152B30		8
150	60	70	20	950	FO153B20		F
150	60	70	25	950	FO153B25		F
160	40	60	20	800	FO160B20		8
160	40	60	25	800	FO160B25		8
160	40	60	30	800	FO160B30		8
175	40	52	20	1000	FO175B20		F
175	40	52	25	1000	FO175B25		F
175	50	52	20	1200	FO176B20		F
175	50	52	25	1200	FO176B25		F



Roue : FONTE

Moyeu : roulements à billes

					REFERENCE		CODE
175	60	65	25	1300	FO177B25		F
175	80	80	30	1600	FO175B30		F
175	100	100	30	2000	FO178B30		F
175	100	100	35	2000	FO178B35		F
200	45	60	20	1000	FO200B20		8
200	50	60	25	1000	FO200B25		8
200	45	60	30	1000	FO200B30		8
200	50	50	20	1400	FO201B20		F
200	50	50	25	1400	FO201B25		F
225	50	65	20	1500	FO225B20		F
225	50	65	25	1500	FO225B25		F
225	60	65	20	1600	FO226B20		F
225	60	65	25	1600	FO226B25		F
225	80	80	30	1800	FO225B30		F
225	100	100	30	2200	FO227B30		F
225	100	100	35	2200	FO227B35		F
250	45	60	25	1200	FO250B25		8
250	45	60	30	1200	FO250B30		8
270	70	70	30	2300	FO270B30		F
270	80	80	30	2400	FO271B30		F
270	100	100	40	3200	FO270B40		F
325	100	100	40	3600	FO325B40		F
325	100	100	50	3600	FO325B50		F
360	125	125	40	4500	FO360B40		F
360	125	125	50	4500	FO360B50		F
370	80	100	40	3500	FO370B40		F
370	80	100	50	3500	FO370B50		F
370	100	100	40	4000	FO371B40		F
370	100	100	50	4000	FO371B50		F
465	100	100	50	4800	FO465B50		F
465	100	100	55	4800	FO465B55		F