








Roue : résine HAUTE TEMPERATURE

Moyeu : Lisse (L)ou à roulements à billes (B)

Temp. D'utilisation : -20°C +280°C intermittent






|  |  |  |  |  | | REFERENCE | CODE |
|---|---|---|---|---|--|-----------|------|
| 80 | 35 | 40 | 12 | 150 | | HT080L12 | F-9 |
| 80 | 35 | 35 | 15 | 160 | | HT080B15 | 9 |
| 100 | 35 | 40 | 12 | 200 | | HT100L12 | F |
| 100 | 35 | 44 | 12 | 200 | | HT101L12 | 9 |
| 100 | 35 | 44 | 15 | 200 | | HT100L15 | 9 |
| 100 | 38 | 38 | 15 | 240 | | HT100B15 | 9 |
| 125 | 40 | 48 | 15 | 250 | | HT125L15 | F |
| 125 | 35 | 44 | 15 | 250 | | HT126L15 | 9 |
| 150 | 50 | 58 | 20 | 275 | | HT150L20 | F-9 |
| 200 | 50 | 58 | 20 | 300 | | HT200L20 | F |
| 200 | 50 | 58 | 20 | 500 | | HT201L20 | 9 |



Roue : POLYAMIDE CHARGE FIBRES DE VERRE

Moyeu : Lisse (L) ou à roulements à billes (B)

Temp. D'utilisation : -20°C +130°C intermittent

|  |  |  |  |  | | REFERENCE | CODE |
|---|---|---|---|---|--|-----------|------|
| 80 | 30 | 40 | 15 | 150 | | NHT080L15 | F |
| 100 | 35 | 40 | 15 | 200 | | NHT100L15 | F |
| 100 | 30 | 45 | 12 | 250 | | NHT100B12 | 9 |
| 125 | 40 | 49 | 15 | 300 | | NHT125L15 | F |
| 125 | 30 | 45 | 12 | 350 | | NHT125B12 | 9 |
| 150 | 40 | 49 | 20 | 380 | | NHT150L20 | F |
| 175 | 50 | 59 | 20 | 550 | | NHT175L20 | F |
| 200 | 50 | 59 | 20 | 600 | | NHT200L20 | F |
| 250 | 60 | 75 | 25 | 1100 | | NHT250L25 | F |








Roue : caoutchouc siliciné

Jante : aluminium

Moyeu : roulements à billes

Temp. D'utilisation : -20°C +250°C intermittent

|  |  |  |  |  | | REFERENCE | CODE |
|---|---|---|---|---|--|-------------|------|
| 100 | 40 | 40 | 15 | 40 | | HTSIL100B15 | 9 |